

# **TOPLI COMMERCIAL WALLCOVERING SPECIFICATIONS**

### **PHYSICAL PROPERTIES**

BACKING MATERIALS: OSNABURG

SURFACE MATERIALS: VINYL COATED, WATER BASED INK
TOTAL WEIGHT: 15 OZ/SQM; 20 OZ/SQM; 25 OZ/SQM
VINYL WEIGHT: 13 OZ/SQM; 18 OZ/SQM; 23 OZ/SQM

BACKING WEIGHT: 2 OZ/SQM

ROLL WIDTH: 110 / 130 / 137 CM ROLL LENGTH: 30 / 50 METERS

OTHER PROPERTIES

WASHABLE, COLORFAST, SCRATCH PROOF

## **FIRE RATING**

USA STANDARD: ASTM E84 CLASS A

FLAME SPREAD: 10 SMOKE DEVELOPED: 10

EUROPE STANDARD:EN13501-1 CLASS B,s1,d0

SMOKE PRODUCTION: S1 FLAME DROPLETS: D0

### **ANTI-MICROBIAL FEATURES**

STANDARD: GB/T2423.16-2008 CLASS 0-1

Topli wallcoverings contain mold resistant additives to resist the growth of mold and mildew under normal conditions. However, wall surface must be clear of mold and no water vapor or moisture infiltration and use only mold-resistant glue and primer while hanging.

### **ECO-FRIENDLY FEATURES**

NO FORMALDEHYDE NO HEAVY METALS LOW VOC CE CERTIFIED

For more detailed specifications, please contact local agent or sellers.